APEM journal

Advances in Production Engineering & Management
Volume 21 | Number 2 | June 2026 | pp 254–267
https://doi.org/10.14743/apem2026.2.572

ISSN 1854-6250
Journal home: apem-journal.org
Original scientific paper

Microstructure-based multiscale prediction of pruning cutter wedge angle for jujube branches

Zhang, S.[a], Wu, S.H.[b,*], Chen, C.[a], Huang, C.L.[a], Jiang, T.T.[a], Zhao, C.L.[a,c], Zhao, Y.H.[c,d], Ciwang, L.[c]

[a]Geely University of China, Chengdu, P.R. China
[b]Sichuan Technology & Business College, Chengdu, P.R. China
[c]Xizang University, Lhasa, P.R. China
[d]Xizang Hydraulic and Electric Planning, Survey and Design Institute, Lhasa, P.R. China

ABSTRACT

The biomechanical properties of jujube branches constitute fundamental parameters for evaluating cutting performance of pruning machinery and optimizing the wedge angle of cutting tools. To investigate how microstructural heterogeneity across different branch regions influences cutting behavior, we integrated X-ray CT imaging with nanoindentation testing. Representative volume elements (RVEs) were constructed from experimentally resolved microstructures to enable multiscale finite element modeling of the pruning process, thereby revealing microscale mechanisms governing cutting resistance. Microstructural characteristics—including porosity, cell wall thickness, and water content—were quantified across five positions along the branch, and their effects on the homogenized (equivalent) shear modulus were systematically evaluated. Results show that both increasing porosity and elevated water content significantly reduce the equivalent shear modulus, with porosity exhibiting a markedly stronger attenuating effect. Crucially, the recommended wedge angle is governed primarily by the ratio of longitudinal-to-transverse shear modulus; based on mechanical sensitivity analysis, the recommended design angle is $\alpha = 21.75°$. This study provides a biomechanical basis for the rational design and performance optimization of specialized pruning tools for jujube trees.

ARTICLEINFO

Keywords:
Jujube branch;
Nanoindentation;
X-ray computed tomography;
Representative volume element;
Multiscale finite element analysis;
Cutting wedge angle;
Pruning machinery

**Corresponding author:*
1529432209@qq.com
(Wu, S.H.)

Article history:
Received 9 September 2025
Revised 3 July 2026
Accepted 7 July 2026

Content from this work may be used under the terms of the Creative Commons Attribution 4.0 International Licence (CC BY 4.0). Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.

References

[1] Zheng, Z., Liu, Y., Dong, J., Zhao, P., Qiao, Y., Sun, S., Huang, Y. (2024). A novel jujube tree trunk and branch salient object detection method for catch-and-shake robotic visual perception, *Expert Systems with Applications*, Vol. 251, Article No. 124022, doi: 10.1016/j.eswa.2024.124022.

[2] Zheng, Z., Hu, Y., Li, X., Huang, Y. (2023). Autonomous navigation method of jujube catch-and-shake harvesting robot based on convolutional neural networks, *Computers and Electronics in Agriculture*, Vol. 215, Article No. 108469, doi: 10.1016/j.compag.2023.108469.

[3] Muthukumaran, S., Sivaramakrishnan, R. (2019). Optimal path planning for an autonomous mobile robot using dragonfly algorithm, *International Journal of Simulation Modelling*, Vol. 18, No. 3, 397-407, doi: 10.2507/IJSIMM18(3)474.

[4] Hu, Y., Zheng, Z., Yu, C., Feng, J., Qiao, Y. (2024). Vibration response characteristics of jujube trees based on finite element method and structure-from-motion, *Scientia Horticulturae*, Vol. 331, Article No. 113125, doi: 10.1016/j.scienta.2024.113125.

[5] Zheng, Z., Hu, Y., Dong, J., Zhao, P., Liu, Y., Jiang, X., Qiao, Y., Sun, S., Huang, Y. (2024). Characterising vibration patterns of winter jujube trees to optimise automated fruit harvesting, *Biosystems Engineering*, Vol. 248, 255-268, doi: 10.1016/j.biosystemseng.2024.11.004.

[6] Zeng, F., Yang, B., Zhao, M., Xing, Y., Ma, Y. (2022). MASANet: Multi-angle self-attention network for semantic segmentation of remote sensing images, *Tehnički Vjesnik – Technical Gazette*, Vol. 29, No. 5, 1567-1575, doi: 10.17559/TV-20220421142959.
[7] Aydin, I., Sevi, M., Akin, E., Güçlü, E., Karaköse, M., Aldarwich, H. (2023). A deep learning-based hybrid approach to detect fastener defects in real-time, *Tehnički Vjesnik – Technical Gazette*, Vol. 30, No. 5, 1461-1468, doi: 10.17559/TV-20221020152721.
[8] Yang, C., Dimyati, K., Mohamad, M. (2024). Detection and classification of railway track surface erosion-caused holes and scratches defects based on YOLOv5s, *Tehnički Vjesnik – Technical Gazette*, Vol. 31, No. 4, 1288-1296, doi: 10.17559/TV-20240422001485.
[9] Peng, F., Zheng, H., Lu, S., Shi, Z., Liu, X., Li, L. (2019). Growth model and visualization of a virtual jujube tree, *Computers and Electronics in Agriculture*, Vol. 157, 146-153, doi: 10.1016/j.compag.2018.12.045.
[10] Ma, X., Zhang, F., Luo, H., Guo, G. (2024). Water shortage detection of jujube trees based on spectral technology and random forest classifier integrated with fractal theory, *Industrial Crops and Products*, Vol. 216, Article No. 118729, doi: 10.1016/j.indcrop.2024.118729.
[11] Mahmood, A., Tiwari, A.K., Singh, S.K. (2024). Maturity grading of jujube for industrial applications harnessing deep learning, *Engineering Computations*, Vol. 41, No. 5, 1171-1184, doi: 10.1108/EC-08-2023-0426.
[12] Zhang, L., Chen, Y., Guo, X., Li, Y., Chen, C., Zou, Y., Zhang, X., Hu, J. (2024). Abnormal phenotypic defects detection of jujube using explainable machine learning enhanced computer vision, *Journal of Food Science*, Vol. 89, No. 11, 7713-7728, doi: 10.1111/1750-3841.17393.
[13] Qiu, X., Xing, W., Que, Y., Lu, G. (2025). Summer pruning in apple trees is an advisable cultural practice that promotes bud differentiation and improves fruit quality: A literature review, *PeerJ*, Vol. 13, Article No. e20229, doi: 10.7717/peerj.20229.
[14] Tong, S., Wang, J., Zhang, J., Liu, L., Wang, Y., Kang, F. (2026). An apple tree pruning robot system based on branch segmentation and decision-making control, *Artificial Intelligence in Agriculture*, Vol. 16, No. 2, 1025-1040, doi: 10.1016/j.aiia.2026.04.005.
[15] Liu, J., Han, X., Mulongoti, C., Ma, Z., Yao, X., Zhuang, Q., Castro-García, S., Du, X. (2025). Vibration dynamics of pruned canopy: Investigating the impact of excitation trajectories on fruit-tree system response, *Biosystems Engineering*, Vol. 257, Article No. 104236, doi: 10.1016/j.biosystemseng.2025.104236.
[16] Cao, Y., Wang, N., Wu, B., Zhang, X., Wang, Y., Xu, S., Zhang, M., Miao, Y., Kang, F. (2025). A novel adaptive cuboid regional growth algorithm for trunk-branch segmentation of point clouds from two fruit tree species, *Agriculture*, Vol. 15, No. 14, Article No. 1463, doi: 10.3390/agriculture15141463.
[17] Win, N.M., Park, J., Kim, S., Lee, Y., Do, V.G., Kwon, J.-G., Kwon, S.-I., Yoo, J., Kang, I.-K., Kweon, H.-J. (2025). Effects of mechanical pruning on tree growth, yield, and fruit quality of 'Arisoo' apple trees, *Agriculture*, Vol. 15, No. 20, Article No. 2118, doi: 10.3390/agriculture15202118.
[18] Chen, Y.Y., Fu, Y.X., Zhang, B., Fu, W., Shen, C.J. (2022). Path planning of the fruit tree pruning manipulator based on improved RRT-Connect algorithm, *International Journal of Agricultural and Biological Engineering*, Vol. 15, No. 2, 177-188, doi: 10.25165/j.ijabe.20221502.6249.
[19] Liu, G., Boom, B., Slob, N., Durodié, Y., Nowé, A., Vanderborght, B. (2026). Automated behavior planning for fruit tree pruning via redundant robot manipulators: Addressing the behavior planning challenge, *IEEE Robotics & Automation Magazine*, Vol. 33, No. 2, 65-75, doi: 10.1109/MRA.2025.3559797.
[20] Gindl, W., Schöberl, T. (2004). The significance of the elastic modulus of wood cell walls obtained from nanoindentation measurements, *Composites Part A: Applied Science and Manufacturing*, Vol. 35, No. 11, 1345-1349, doi: 10.1016/j.compositesa.2004.04.002.
[21] Huang, Y., Fei, B., Wei, P., Zhao, C. (2016). Mechanical properties of bamboo fiber cell walls during the culm development by nanoindentation, *Industrial Crops and Products*, Vol. 92, 102-108, doi: 10.1016/j.indcrop.2016.07.037.
[22] Keryvin, V., Lan, M., Bourmaud, A., Parenteau, T., Charleux, L., Baley, C. (2015). Analysis of flax fibres viscoelastic behaviour at micro and nano scales, *Composites Part A: Applied Science and Manufacturing*, Vol. 68, 219-225, doi: 10.1016/j.compositesa.2014.10.006.
[23] Stevanic, J.S., Salmén, L. (2009). Orientation of the wood polymers in the cell wall of spruce wood fibres, *Holzforschung*, Vol. 63, No. 5, 497-503, doi: 10.1515/HF.2009.094.
[24] Stubbs, C.J., Sun, W., Cook, D.D. (2019). Measuring the transverse Young's modulus of maize rind and pith tissues, *Journal of Biomechanics*, Vol. 84, 113-120, doi: 10.1016/j.jbiomech.2018.12.028.
[25] Malaga-Toboła, U., Łapka, M., Tabor, S., Niesłony, A., Findura, P. (2019). Influence of wood anisotropy on its mechanical properties in relation to the scale effect, *International Agrophysics*, Vol. 33, No. 3, 337-345, doi: 10.31545/intagr/110808.
[26] Malek, S., Gibson, L.J. (2017). Multi-scale modelling of elastic properties of balsa, *International Journal of Solids and Structures*, Vol. 113-114, 118-131, doi: 10.1016/j.ijsolstr.2017.01.037.
[27] Masood, A.A., Ali, A., Madhu, P., Yashas Gowda, T.G., Jeevan, T.P., Sharath, B.N. (2024). Characterizing the effects of SiC and Al_2O_3 on the mechanical properties of Al6082 hybrid metal matrix composites: An experimental and neural network approach, *Advances in Production Engineering & Management*, Vol. 19, No. 2, 281-292, doi: 10.14743/apem2024.2.507.
[28] Vievesis, M., Kujalavicius, Z., Keturakis, G., Gyliene, V., Jablonskyte, J. (2025). Impact of machining parameters on surface roughness in CNC hardwood milling: A multivariate approach, *Advances in Production Engineering & Management*, Vol. 20, No. 2, 191-204, doi: 10.14743/apem2025.2.535.
[29] Faisal, T.R., Hristozov, N., Western, T.L., Rey, A.D., Pasini, D. (2014). Computational study of the elastic properties of Rheum rhabarbarum tissues via surrogate models of tissue geometry, *Journal of Structural Biology*, Vol. 185, No. 3, 285-294, doi: 10.1016/j.jsb.2014.01.012.

[30] Sevšek, L., Vilkovský, S., Majerníková, J., Pepelnjak, T. (2024). Predicting the deep drawing process of TRIP steel grades using multilayer perceptron artificial neural networks, *Advances in Production Engineering & Management*, Vol. 19, No. 1, 46-64, doi: 10.14743/apem2024.1.492.
[31] Rosnitschek, T., Hueter, F., Alber-Laukant, B. (2020). FEM-based modelling of elastic properties and anisotropic sinter shrinkage of metal EAM, *International Journal of Simulation Modelling*, Vol. 19, No. 2, 197-208, doi: 10.2507/IJSIMM19-2-509.
[32] Saavedra Flores, E.I., Friswell, M.I. (2012). Multi-scale finite element model for a new material inspired by the mechanics and structure of wood cell-walls, *Journal of the Mechanics and Physics of Solids*, Vol. 60, No. 7, 1296-1309, doi: 10.1016/j.jmps.2012.03.007.
[33] Zhou, F., Huang, J., Liu, W., Deng, T., Jia, Z. (2019). Multiscale simulation of elastic modulus of rice stem, *Biosystems Engineering*, Vol. 187, 96-113, doi: 10.1016/j.biosystemseng.2019.09.003.
[34] Al-Zube, L., Sun, W., Robertson, D., Cook, D. (2018). The elastic modulus for maize stems, *Plant Methods*, Vol. 14, Article No. 11, doi: 10.1186/s13007-018-0279-6.
[35] Zhao, D., Shi, W., Xia, X., Tang, Y., Tao, J. (2020). Microstructural and lignin characteristics in herbaceous peony cultivars with different stem strengths, *Postharvest Biology and Technology*, Vol. 159, Article No. 111043, doi: 10.1016/j.postharvbio.2019.111043.
[36] Qing, H., Mishnaevsky, L. (2011). A 3D multilevel model of damage and strength of wood: Analysis of microstructural effects, *Mechanics of Materials*, Vol. 43, No. 9, 487-495, doi: 10.1016/j.mechmat.2011.05.007.
[37] Arzola-Villegas, X., Plaza, N.Z., Bechle, N.J., Wang, Y., Lakes, R., Stone, D.S., Jakes, J.E. (2025). Moisture-dependent transverse isotropic elastic constants of wood S2 secondary cell wall layers determined using nanoindentation, *Forests*, Vol. 16, No. 5, Article No. 712, doi: 10.3390/f16050712.
[38] Kovács, Á., Kerényi, G. (2019). Physical characteristics and mechanical behaviour of maize stalks for machine development, *International Agrophysics*, Vol. 33, No. 4, 427-436, doi: 10.31545/intagr/113335.
[39] Wójtowicz, T., Grabowska-Joachimiak, A., Zieliński, A. (2020). Analysis of morpho-anatomical stem properties determining its mechanical strength in selected rye cultivars, *International Agrophysics*, Vol. 34, No. 1, 123-131, doi: 10.31545/intagr/115096.
[40] Steele, J.H., Ifju, G., Johnson, J.A. (1976). Quantitative characterization of wood microstructure, *Journal of Microscopy*, Vol. 107, No. 3, 297-311, doi: 10.1111/j.1365-2818.1976.tb02450.x.
[41] Rabbani, H., Sohraby, N., Gholami, R., Jaliliantabar, F., Waismorady, A. (2015). Determination of mass density module, crush resistance coefficient and cutting efficiency of rose (Rosa Damascene Mill), *Scientia Horticulturae*, Vol. 190, 144-148, doi: 10.1016/j.scienta.2015.02.009.
[42] Ju, P. (2023). Optimizing rock breaking performance: The influence of chamfer on polycrystalline diamond compact (PDC) cutters, *Advances in Production Engineering & Management*, Vol. 18, No. 4, 417-433, doi: 10.14743/apem2023.4.482.
[43] Johnson, P.C., Clementson, C.L., Mathanker, S.K., Grift, T.E., Hansen, A.C. (2012). Cutting energy characteristics of *Miscanthus x giganteus* stems with varying oblique angle and cutting speed, *Biosystems Engineering*, Vol. 112, No. 1, 42-48, doi: 10.1016/j.biosystemseng.2012.02.003.